

HIGH QUALITY VALVES FOR GAS CYLINDERS



COMPANY

Svarrnim Forgings is a group company to Svarrnim Infrastructures Pvt. Ltd. one of the leading companies in India for the last 38 years. With production facilities carried in Delhi NCR (India), Svarrnim Forgings is capable of manufacturing and testing high-quality LPG valves. S.F. valves are manned by a team that has both experience and expertise in the market domain thus making and delivering the best quality valves.

PRODUCTS



COMPACT VALVE WITH INBUILT DUST CAP

INLET: W28.8 DIN 477, 3/4" - 14 NGT, W19.8 DIN 477, M26.0X1.5-6G, Ø19.3X1.814 & Ø23.2X2.0
OUTLET: 20MM, 21MM, 22MM, 25.6MM, 27MM
PRV: 26 BAR, FLOW CAPACITY 3M³/4M³/5M³/10M³ AIR/MIN

CUSTOMIZATION AVAILABLE AS PER BUYER'S REQUIREMENTS



DUAL SEAL VALVE / SNAP TIGHT VALVE

INLET: W28.8 DIN 477, 3/4" - 14 NGT, W19.8 DIN 477, M26.0X1.5-6G, Ø19.3X1.814 & Ø23.2X2.0
OUTLET: 27.00MM
PRV: 26 BAR, FLOW CAPACITY 3M³/4M³/5M³/10M³ AIR/MIN

CUSTOMIZATION AVAILABLE AS PER BUYER'S REQUIREMENTS



VALVE FOR COMPOSITE CYLINDERS

INLET: M26X1.5, M34X2
OUTLET: 20MM, 21MM, 22MM, 25.6MM, 27MM
PRV: 26 BAR, FLOW CAPACITY 3M³/4M³/5M³/10M³ AIR/MIN

CUSTOMIZATION AVAILABLE AS PER BUYER'S REQUIREMENTS



LIQUID OFF TAKE VALVE

INLET: 3/4" - 14 NGT, W28.8 DIN 477, M26.0X1.5-6G
OUTLET: 1 - 1/4" - 5 ACME 2G
CONNECTION NO. 790 (CGA V-1)
PRV: 26 BAR, FLOW CAPACITY 3M³/4M³/5M³/10M³/12.75M³ AIR/MIN

CUSTOMIZATION AVAILABLE AS PER BUYER'S REQUIREMENTS



LCC 27 VALVE

INLET: 3/4" - 14 NGT
OUTLET: 0.885 - 14 UNS - LH, 1.312 - 5 ACME - 2G
PRV: 26 BAR, FLOW CAPACITY 3M³/4M³/5M³/10M³ AIR/MIN

CUSTOMIZATION AVAILABLE AS PER BUYER'S REQUIREMENTS



QCC VALVE WITH OPD

INLET: 3/4" - 14 NGT
OUTLET: 0.885 - 14 UNS - LH, 1.312 - 5 ACME - 2G
PRV: 26 BAR, FLOW CAPACITY 3M³/4M³/5M³/10M³ AIR/MIN

CUSTOMIZATION AVAILABLE AS PER BUYER'S REQUIREMENTS



FORKLIFT VALVE

INLET: 3/4" - 14 NGT, W28.8 DIN 477
OUTLET: 1 - 1/4" - 5 ACME 2G
CONNECTION NO. 790 (CGA V-1)
PRV: 26 BAR, FLOW CAPACITY
3M³/4M³/5M³/10M³/12.75M³ AIR/MIN

CUSTOMIZATION AVAILABLE AS PER BUYER'S REQUIREMENTS



CAMPING VALVES

INLET: M22X1.25MM
OUTLET: M16.0X1.5MM (TECH TYPE)
M16.0X1.5MM (HEX TYPE)

CUSTOMIZATION AVAILABLE AS PER BUYER'S REQUIREMENTS



COMPACT VALVES WITH
SAFETY RELIEF

INLET: W28.8 DIN 477, 3/4" - 14 NGT
W19.8 DIN 477, Ø26.2X2.0, Ø19.3X1.814
& Ø23.2X2.0
OUTLET: FROM Ø20.0MM TO Ø27.0MM
PRV: 26 BAR, FLOW CAPACITY
3M³/4M³/5M³/10M³ AIR/MIN

CUSTOMIZATION AVAILABLE AS PER BUYER'S REQUIREMENTS



DUAL PORT VALVES

INLET: 3/4" - 14 NGT, W28.8 DIN 477
OUTLET: LIQUID CONNECTION 0.625" - 18 UNF
2A-RH-EXT 3/8" SAE FLARE (MALE) (CGA V-1)
VAPOUR CONNECTION G 5/8" - 14 BSPF - LH
PRV: 26 BAR, FLOW CAPACITY
3M³/4M³/5M³/10M³/12.75M³ AIR/MIN

CUSTOMIZATION AVAILABLE AS PER BUYER'S REQUIREMENTS



HANDWHEEL TYPE VALVES
(FRENCH TYPE)

INLET: W28.8 DIN 477, 3/4" - 14 NGT
W19.8 DIN 477, M26.0X1.5-6G,
Ø19.3X1.814 & Ø23.2X2.0
OUTLET: W20.0X1.81 4- LH, Ø21.7X1.814 -
LH G5/8 - 14BSP - LH, 0.885" - 14NGO - LH
& W21.8X1.814 - LH DIN477

CUSTOMIZATION AVAILABLE AS PER BUYER'S REQUIREMENTS



JUMBO VALVES

INLET: W28.8 DIN 477, 3/4" - 14 NGT
W19.8 DIN 477, M26.0X1.5-6G,
Ø19.3X1.814 & Ø23.2X2.0
OUTLET: Ø35.0 MM
PRV: 26 BAR, FLOW CAPACITY 3M³/4M³/
5M³ AIR/MIN
28 BAR, FLOW CAPACITY 4M³ AIR/MIN

CUSTOMIZATION AVAILABLE AS PER BUYER'S REQUIREMENTS



COMPACT SELF CLOSE VALVES/
QUICK COUPLING VALVES

INLET: W28.8 DIN 477, 3/4" - 14 NGT
W19.8 DIN 477, M26.0X1.5-6G,
Ø19.3X1.814 & Ø23.2X2.0,
OUTLET: 19MM, 20MM, 21MM, 22MM,
25.6MM, 27MM

CUSTOMIZATION AVAILABLE AS PER BUYER'S REQUIREMENTS



CAMPING VALVES WITH
REGULATING NOB

INLET: 1/2" - 14 NGT 60°, 1:16 (CGA V-1),
W28.8 DIN 477, 3/4" - 14 NGT W19.8 DIN 477,
Ø26.2X2.0, Ø19.3X1.814 & Ø23.2X2.0
OUTLET: G 3/8, BSPF-RH, W20.0X1.81 4- LH,
W21.8X1.814 - LH DIN477
PRV: 26 BAR, FLOW CAPACITY
3M³/4M³/5M³ AIR/MIN

CUSTOMIZATION AVAILABLE AS PER BUYER'S REQUIREMENTS



POL VALVES/HAND
WHEEL VALVES WITH
SAFETY RELIEF

INLET: 3/4"-14 NGT W19.8 DIN 477, W28.8 DIN
477, M26.0X1.5-6G, Ø19.3X1.814 & Ø23.2X2.0
OUTLET: G5/8-14BSP LH, 0.885"-14NGO-LH,
Ø21.7X1.814-LH, W20.0X1.81 4-LH
& W21.8X1.814-LH DIN477
PRV: 26 BAR, FLOW CAPACITY
3M³/4M³/5M³/10M³/12.75M³ AIR/MIN

CUSTOMIZATION AVAILABLE AS PER BUYER'S REQUIREMENTS



BUNGS

ALSO KNOW AS

NECK RINGS, NECKERS, SOCKETS, FLANGE, VALVE NECK, VALVE BOSS, VALVE PAD, COLLERETTE

NGT THREADS, DIN 477 THREADS, ISO THREADS, M22 X 1.25 [FOR 3 & 6 KGS CYLINDER], 25.4 MM X TAPER 1:8
[FOR REFRIGERANT GAS CYLINDER]



EXPORTING ACROSS THE GLOBE

Our production facility situated in capital of India (Delhi) gives us the privilege of exporting the goods on time delivery.

Our long holding relationships with reputed forwarders of India stands as our pillar in importing the components from accross the globe and dispatching the goods on time at any location on the globe.



Contact Info

Mr. Abhay Garg
Founder & CEO



+91 880 0194 269 info@svarnimforgings.com sales@svarnimforgings.com



Head Office

308, Ocean Complex, Sector 18, Noida,
Gautam Budh Nagar, Uttar Pradesh 201301



Factory Office

C-29, Site-C, Surajpur Industrial Area,
Greater Noida, Gautam Budh Nagar,
Uttar Pradesh 201308

www.svarnimforgings.com